SYNYON

Document No. SYN-DS-SYF4015
Revision V2.0 | 2026-11-02

Molded Power Inductor

SYF4015 Series

Flat Series · 4.0×4.0×1.6 mm



RoHS Compliant · Halogen-Free

Features

- **Ultra-low profile, only 1.5 mm high**
- **Ultra-low DCR, excellent current handling, soft saturation**

Core material:	Composite magnetic powder
Environmental:	RoHS compliant, halogen-free
Terminal plating:	Ni-Sn (SN); SAC/SP optional
Anti-corrosion:	Terminal anti-corrosion plating
Operating temperature:	-40°C to +125°C
Max. part temperature:	+165°C (ambient + rise)
Storage temperature:	-55°C to +165°C (part); -55 to +80°C (reel)
Reflow soldering:	Max. 3 cycles, 260°C / 40 s
MSL level:	Level 1, unlimited floor life
Rated voltage:	20V

Electrical Specifications

(Ta = 25°C)


Part Number	Inductance ±20% (μH)	DCR (mΩ) typ/max	SRF typ (MHz)	Isat (A) 10%/20%/30%	Irms (A) 20℃/40℃
SYF4015-181MSN	0.18	4.2 / 4.7	150	6.2 / 8 / 8.5	12 / 14.5
SYF4015-331MSN	0.33	6.8 / 7.5	112	5.5 / 7 / 7.5	9.6 / 13.2
SYF4015-471MSN	0.47	7.6 / 8.36	89	3.5 / 5.4 / 6.6	9.1 / 11.2
SYF4015-701MSN	0.7	9.5 / 10.45	70	3.3 / 5.3 / 6.3	7.2 / 10.1
SYF4015-122MSN	1.2	18.8 / 20.7	61	2.6 / 3.7 / 4.5	5.1 / 7.1


1. Inductance is measured at 1 MHz, 0.1 Vrms, 0 Adc, Ta = 25°C.
2. DCR is measured with a DC milliohm meter.
3. SRF is measured with a high-precision network analyzer.
4. Isat: DC current at which inductance drops by the stated percentage at 25°C; derating is required for high-temperature applications.
5. Irms: DC current causing the stated temperature rise (20°C/40°C). For reference only; verify by measurement in the end application.
6. Termination codes: SN = tin-nickel, SAC = tin-silver-copper; SP = tin-lead (non-RoHS).
7. Packaging: tape and reel, compliant with EIA-481; 7-inch and 13-inch reels available.
8. Electrical data are specified at Ta = 25°C. Specifications are subject to change without notice.


Xinyuan Technology (Shenzhen) Co., Ltd. Longgang Branch
Address: No. 5002-1, Longgang Avenue (Longgang Section), Longgang District, Shenzhen
Tel: 400-855-8758 | E-mail: sales@synyon.com | Web: https://www.synyon.com

Specifications subject to change without notice
Please refer to the latest version on our website

Performance Curves











Test Condition: Ta=25℃, JEDEC standard PCB, natural convection. Curves derived from typical specifications for reference only.


Inductance vs DC Current













Note: Curves are plotted from Isat test points; actual performance shall be verified on the final product.

Dimensions & Recommended Land Pattern



Symbol	Parameter	Min	Typ	Max
L	Body Length (mm)	3.70	4.00	4.30
W	Body Width (mm)	3.70	4.00	4.30
H	Body Height (mm)	/	/	1.6
Wt	Weight (g)	0.128	0.132	0.136

Packaging



Parts per reel		Reel dimensions (mm)				Tape dimensions (mm)						
7" (178 mm)	13" (330 mm)	A	B	C	D	E	W	P	Po	P1	H	T
1000	4000	178/330	60/100	13	14.7	12.4	12	8	4	2	1.78	0.23

Packing method: Tape and reel, compliant with EIA-481

Quantity: 7" reel: 1000 pcs; 13" reel: 4000 pcs

Tape spec: Embossed carrier tape; dimensions per actual packing

Features & Applications

Features

· Ultra-low profile, only 1.5 mm high
· Ultra-low DCR, excellent current handling, soft saturation

Applications

· Slim notebooks, tablets and smartphone mainboard supplies
· Wearable devices and portable electronics
· High-density DC-DC modules and point-of-load converters
· Automotive slim modules and industrial control boards